



**ITA** Le porte rapide flessibili DynamicRoll® Frigo 2 sono studiate per il settore celle frigorifere, esse mettono in relazione sia la velocità di passaggio che la funzionalità di apertura.

In queste zone vi è grande necessità di evitare al massimo le dispersioni e mantenere le temperature all'interno delle celle, senza privarsi del facile passaggio da una zona ad un'altra (+1 C° a -30 C°).

Consigliata in ambienti ad alta umidità. Si consiglia l'utilizzo della porta DynamicRoll® Frigo 2 in abbinamento al portone frigorifero scorrevole.



## DYNAMICROLL® FRIGO 2

[www.frigo2-doors.com](http://www.frigo2-doors.com)



**FOR YOUR ENERGY  
SAVING  
FROM +1° TO -30°**



### Scheda Tecnica DynamicRoll® Frigo 2 Technical Data DynamicRoll® Frigo 2

Max Dimensioni (L x H) / Max Size (WxH)	4500 x 4500 mm
Velocità di apertura / Opening Speed	~ 1,0 m/sec (max)
Velocità di chiusura / Closing Speed	~ 0,8 m/sec
Resistenza al vento / Wind load [EN 12424] fino a L / until to W 4500 x 4500 mm L / W 3000 x 3000 mm L / W 5000 x 5000 mm L / W 7000 x 5000 mm L / W 8000 x 8000 mm	Classe / Class 1 ✓ 1 ✓ ... ... ...
Alimentazione / Power Supply	400 V, 16A* 3 phase
Frequenza / Frequency	50/60 Hz
Quadro di comando / Control Box	Inverter
Finecorsa / Drive	Encoder
Teli PVC / PVC Curtain	2 x 0,9 mm - 900 gr/m <sup>2</sup>
Costa di Sicurezza / Safety Edge [EN 13241]	Sensore antischacciamento / Anti-Crash Safety Sensor
Struttura / Frame	Acciaio zincato o Inox, Verniciata / Galvanized or Stainless Steel, Painted
Cicli di vita / Performance Cycles	1.000.000
Distanza tra i 2 Teli / Distance between curtains	250 mm
Trasmittanza termica / Heat Transfer	fino a 2,52 W/m <sup>2</sup> K / until to 2,52 W/m <sup>2</sup> K
+ info Test PVC / + info PVC Test	sul catalogo specifico dei PVC / on the specific catalogue of PVC

**ENG** The new BMP EUROPE product of rapid doors, a double curtain for low temperatures, is the flexible door which solves the easy transition from areas of high temperature difference without creating a loss in temperature between each room. The Frigo 2 is the ideal door to separate freezers and chilled areas.

BMP EUROPE DynamicRoll® Frigo 2 rapid doors contain two types of applied technology for a better thermal insulation, a physical barrier with a double curtain system and a heater blower between these curtains. These rapid doors for cold stores operate fast to ensure the minimum of temperature loss between the 2 areas which in turn saves energy and money (example: area +1° to area -30°).

BMP EUROPE provides a Great product with Great service. Contact us for more information.

The industrial doors made by BMP EUROPE are unique and not repeatable, always be wary of copies.