



OCTO



The hoist that is designed for the toughest jobs.



Main Features

- Easy and fast self reeving hoist
- Modular construction for ease of maintenance and interchanging power attachments
- Thermal overload to protect against overheating
- Fail safe primary brake positively locked with power switch in off position
- Hoist mounted, pendant and central control available
- Low rope wear factor, no point loads to overstress wire
- Independent secondary Safety Brake with manual trip and reset lever
- Emergency descent at controlled speed possible when the primary brake is released

Options

- Overload/underload to protect against platform overloading
- Top limit switch stops ascent at preset height
- Anti-tilt device ensures platform does not tilt beyond preset maximum
- Other power supplies upon request

Specifications

Power Supply	Safe Working capacity	Climbing speed	Power consumption	Selfweight	Recommended steel wire rope
3~240V/50Hz	800 kg	8,5m/min	3,6 Amp	70 kg	4 x 36 WS Polyprop core 9mm
3~400V/50Hz	800 kg	8,5m/min	2,6 Amp	70 kg	4 x 36 WS Polyprop core 9mm
Air	800 kg	8,5m/min	2m/min at 6,5 bar	54 kg	4 x 36 WS Polyprop core 9mm
3~400V/50Hz	1.000 kg	8,5 m/min	Start 11 Amp Running 4 Amp	75 kg	12x17 special compacted 9mm

